Argonne Pational Laboratory

LABORATORY INVESTIGATIONS IN SUPPORT OF FLUID BED FLUORIDE VOLATILITY PROCESSES

Part VI

- A. The Absorption Spectrum of Plutonium Hexafluoride
- B. Analysis of Mixtures of Plutonium Hexafluoride and Uranium Hexafluoride by Absorption Spectrometry

by

Martin J. Steindler and William H. Gunther

LEGAL NOTICE

This report was prepared as an account of Government sponsored work. Neither the United States, nor the Commission, nor any person acting on behalf of the Commission:

- A. Makes any warranty or representation, expressed or implied, with respect to the accuracy, completeness, or usefulness of the information contained in this report, or that the use of any information, apparatus, method, or process disclosed in this report may not infringe privately owned rights; or
- B. Assumes any liabilities with respect to the use of, or for damages resulting from the use of any information, apparatus, method, or process disclosed in this report.

As used in the above, "person acting on behalf of the Commission" includes any employee or contractor of the Commission, or employee of such contractor, to the extent that such employee or contractor of the Commission, or employee of such contractor prepares, disseminates, or provides access to, any information pursuant to his employment or contract with the Commission, or his employment with such contractor.

ANL-6817 Chemistry (TID-4500, 28th Ed.) AEC Research and Development Report

ARGONNE NATIONAL LABORATORY 9700 South Cass Avenue Argonne, Illinois 60440

LABORATORY INVESTIGATIONS IN SUPPORT OF FLUID BED FLUORIDE VOLATILITY PROCESSES

PART VI

- A. THE ABSORPTION SPECTRUM OF PLUTONIUM HEXAFLUORIDE
- B. ANALYSIS OF MIXTURES OF PLUTONIUM HEXAFLUORIDE AND URANIUM HEXAFLUORIDE BY ABSORPTION SPECTROMETRY

by

Martin J. Steindler and William H. Gunther

Chemical Engineering Division

January 1964

Part I of this series is ANL-6742 Part II of this series is ANL-6753 Part III of this series is ANL-6762 Part IV of this series is ANL-6763 Part V of this series is ANL-6812

Operated by The University of Chicago under Contract W-31-109-eng-38 with the U. S. Atomic Energy Commission




TABLE OF CONTENTS

		<u>Pa</u>	ge
ABS	TRAC	ZT	3
I.		ABSORPTION SPECTRUM OF PLUTONIUM	3
	Α.	Introduction	3
	В.	Experimental	4
	C.	Results and Discussion	6
		1. Results	6
II.	AND	LYSIS OF MIXTURES OF PLUTONIUM HEXAFLUORIDE URANIUM HEXAFLUORIDE BY ABSORPTION CTROMETRY	10
	Α.	Introduction	10
	В.	Experimental	11
	C.	Results and Discussion	11
AC	KNOW	LEDGMENT	14
BIE	BLIOG	RAPHY	15

TABLE OF CONTENTS

PEGE PEGE RECTANCE AND PROTOCOLUMN SECTIONS SECT

Experimental
C. Results and Discussion
P. Results
2. Discussion
C. Discussion

ANALYSIS OF MIXTURES OF PLUTONIUM HEXAPLUORIDE AND VRANIUM HEXAPLUORIDE BY ABSORPTION SPECIROMETRY.

A. Introduction.

C. Results and Discussion .

ACIGNOWLEDGMENT

BIBLIOGRAPHY

LIST OF FIGURES

No.	<u>Title</u>	Page
1.	Spectral Cells for Use with Corrosive Gases. Top Figure - 1-cm Cell; Bottom Figure - 10-cm Cell	5
2.	Absorption Spectrum of Gaseous Plutonium Hexafluoride	7
3.	Beer's Law Plot for Gaseous Plutonium Hexafluoride at 3157 Å	9
4.	Beer's Law Plot for Gaseous Plutonium Hexafluoride at 10075 Å	9
5.	$\epsilon_{\mathbf{m}}$ of PuF ₆ -UF ₆ Mixtures at 10075 Å	12
6.	$\epsilon_{ m m}$ of PuF ₆ -UF ₆ Mixtures at 3157 Å	13
	LIST OF TABLES	
No.	<u>Title</u>	Page
1.	Absorption Spectrum of Gaseous Plutonium Hexafluoride	8
2.	Peak Separations for Several Bands in the Absorption Spectrum of Gaseous Plutonium Hexafluoride	9
3.	Determination of the Molar Absorbancy Index for Mixtures of PuF ₆ and UF ₆	12

MARY OF PARTIES

Spectral Cells for Use with Corrusive Cases Top Fig.

Absorption Spectrum of Gascous Platenium Rexafineride.

Beer's Law Plot for Gascous Platonium Heinfluoride at

Beer's Law Plot for Casedus Phitoman Hexafluoride at 10875 A

Em of Por, -Ur, Mixtures at 10075 A.

em of Pull - Ull Mixtures at 3157 A .

LIST OF TABLES

BERLE

Absorption Spectrum of Cascous Plutonium Hexafluoride.

Peak Separations for Several Bands in the Absorption

Determination of the Molar Absorbancy Index for Mixtures

LABORATORY INVESTIGATIONS IN SUPPORT OF FLUID BED FLUORIDE VOLATILITY PROCESSES

Part VI

- A. The Absorption Spectrum of Plutonium Hexafluoride
- B. Analysis of Mixtures of Plutonium Hexafluoride and Uranium Hexafluoride by Absorption Spectrometry

by

Martin J. Steindler and William H. Gunther

ABSTRACT

The absorption spectrum of gaseous plutonium hexafluoride was determined over the range of wavelengths from 2000 Å to 26,000 Å, and molar absorbancy indices were calculated. A test of the spectral method of analysis of plutonium hexafluoride in mixtures of plutonium hexafluoride and uranium hexafluoride was made. The results indicate that plutonium hexafluoride may be determined in mixtures containing uranium hexafluoride by use of a spectral method although care is required to pretreat the cell windows to avoid reaction with plutonium hexafluoride.

I. THE ABSORPTION SPECTRUM OF PLUTONIUM HEXAFLUORIDE

A. Introduction

The properties of plutonium hexafluoride are of interest both from a fundamental viewpoint related to the properties of hexafluorides of the transition elements and from an applied viewpoint related to separations processes for spent reactor fuels.

The Fluoride Volatility Process utilizes the volatility of the pertinent fluorides to obtain a separation of the actinides from fission products. In connection with the separations process, the spectral properties of plutonium hexafluoride have been investigated to evaluate the applicability of spectral data to the analysis of gaseous mixtures containing plutonium hexafluoride. Owing to the fact that no adequate data on the molar absorbancy indices at various wavelengths exist, a detailed determination of the spectrum of gaseous plutonium hexafluoride was carried out in the ultraviolet, visible, and the near-infrared regions.

LABORATORY INVESTIGATIONS IN SUPPORT OF FLUID RED FLUORIDE VOLATILITY PROCESSES

IV. Frag

- A. The Absorption Spectrum of Plutomum Haxafluoride
- B. Analysis of Mixtures of Platonium Hexafluoride and Uranium Hexafluoride by Absorption Spectrometry

Ŵď

Mayten J. Stemdler and William H. Gunther

ABSTRACT

The absorption spectrum of gaseous pintonium hexafluoride was determined over the range of wavelengths from
2000 Å to 26,000 Å, and molar absorbancy indices were calculated. A test of the spectral method of analysis of plutonium hexafluoride is mixtures of plutonium hexafluoride and
uranium hexafluoride was made. The results indicate that
plutonium hexafluoride may be determined in mixtures containing uranium hexafluoride by use of a spectral method
although care is required to pretreat the cell windows to
avoid reaction with plutonium hexafluoride.

THE ABSORPTION SPECTRUM OF FLUTONIUM HEXAFLUORIDE

A. Introduction

The properties of plutonium hexafluoride are of interest both from a fundamental viewpoint related to the properties of hexafluorides of the transition elements and from an applied viewpoint related to separations processes for spent reactor fuels.

The Fluoride Volatility Process utilizes the solatility of the pertunent fluorides to obtain a separation of the actinides from fission products. In connection with the separations process, the spectral properties of plustonium hazafluoride have been investigated to evaluate the applicability of spectral data to the analysis of gaseous mixtures containing plutomium hazafluoride. Owing to the fact that no adequate data on the molar absorbancy indices at various wavelengths exist, a detailed determination of the spectrum of gaseous plutomium hexafluoride was carried out in the diravfolet, visible, and the near-infrared regions.

B. Experimental

The plutonium hexafluoride used in the determination of the spectra was prepared by the reaction of plutonium dioxide or plutonium tetrafluoride and elemental fluorine at about 550°C in nickel equipment. (1) The volatile plutonium hexafluoride was collected in a trap cooled to -80°C and purified by trap-to-trap vacuum distillation.

Prior to each spectral determination, the fluorine formed in the decomposition of plutonium hexafluoride by its own alpha radiation was removed by evacuation while plutonium hexafluoride was cooled to -80°C. The purity of the samples was determined by vapor pressure measurements at several temperatures. In all cases, the measured vapor pressures agreed with those reported in the literature.(2)

Spectral cells were constructed from $l \frac{1}{4}$ -in.-diameter Monel pipe of various lengths, threaded at each end to receive a brass retaining ring which held a Teflon gasket, a 3-mm-thick quartz window, and another Teflon gasket. Cell lengths of 1, 5, and 10 cm were used. A small valve* containing a flare fitting was welded into the body of the cell. Figure 1 shows the construction of the spectral cells.

Prior to use, each cell was thoroughly cleaned and checked for leaks with a helium mass-spectrometer leak detector. In addition, each cell was treated with elemental fluorine at room temperature for several hours, followed by treatment with plutonium hexafluoride for 15 min before being used with plutonium hexafluoride.

Samples were introduced by expansion of the gas into the evacuated cells. In all instances, the time plutonium hexafluoride was in contact with the spectrophotometer cells was kept to a minimum to avoid deposition of plutonium tetrafluoride on the quartz windows. It was observed, however, that even with these precautions, a small amount of powdered plutonium tetrafluoride was present in the cell after a few determinations. The absorbance of the empty cells in the ultraviolet region usually increased slightly with each exposure to plutonium hexafluoride. The absorbance of the empty cell in the visible and near-infrared regions remained unaffected by pretreatment and exposure to plutonium hexafluoride.

Auxiliary equipment used in this work consisted of a vacuum manifold, storage vessels and traps, all constructed of nickel. Except for the valves used on the cells, valves with nickel diaphragms** were used throughout. The major portion of the equpment was housed in a Blickman Type K hood which had been modified for use with plutonium by replacement of the

^{*} Hoke type 1479.


^{**} Hoke type 413A or type 413.


sorbance of the empty cells in the ultraviole region usually increased

sliding front with a plastic panel containing three glove rings. (3) A $\frac{1}{4}$ -in. nickel tube, terminating outside the hood in a valve and flare fitting, was used to attach the spectral cell to the apparatus. Although the cell was repeatedly disconnected from the apparatus at the flare fitting, use of careful experimental techniques avoided any detectable quantities of plutonium from entering the room.

Figure 1

SPECTRAL CELLS FOR USE WITH CORROSIVE GASES
TOP FIGURE - 1-cm CELL; BOTTOM FIGURE - 10-cm CELL






silding front with a plastic panel continuing three glove rings. (3) A $\frac{1}{4}$ -in, mickel tupe, terminating outside the bood in a valve and flare fitting, was need to intech the spectral cell to its apparatus. Although the cell was repeatedly disconnected from the apparatus at the flare fitting, use of each experimental techniques avoided any detectable quantities of plutonium from entertus the room.

Figure 1

SPECIFAL CELLS FOR USE WITH CORROSIVE CASES - TO FIGURE - 10-cm CELLS BOITON FIGURE - 10-cm CELLS



Pressures were determined by use of a Booth-Cromer (4) pressure transmitter and self-balancing relay which was operated as a null indicator and was connected to a Heise precision gage.

A Cary, Model 14 double-beam, recording spectrophotometer was used for this work. The wavelength calibration of the instrument was checked against a mercury arc and was found to deviate only very slightly from the literature values reported for the mercury arc.(5) In order to counteract the increasing absorption by the empty cell, particularly in the ultraviolet, an empty cell which had been exposed to plutonium hexafluoride was used in the reference beam of the spectrophotometer when determining the ultraviolet spectrum. The spectrophotometer recorded the value of absorbance (log I_0/I) directly.

The concentration of plutonium hexafluoride in the cell in units of moles per liter was calculated from the observed pressure and temperature. All spectral determinations were carried out at ambient laboratory temperatures. Molar absorbancy indices (molar extinction coefficients) were calculated from the measured absorbance and the calculated concentrations, according to the equation

$$\log I_0/I = \epsilon \ell c$$
,

where $\log I_0/I$ is the absorbance (optical density), ϵ is the molar absorbancy index in liters mole⁻¹ cm⁻¹, c the concentration in moles liter⁻¹, and ℓ is the thickness of the absorbing medium or the length of the light path in the sample. The latter was obtained from a knowledge of the dimensions of the nickel cell and the thickness of the compressed gaskets sealing the quartz windows to the body of the cell. Values for the absorbance were corrected for the absorption of the empty cell by using the arithmetic average of the absorbance of the empty cell as determined before and after each determination of the spectrum.

C. Results and Discussion

1. Results

The absorption spectrum of gaseous plutonium hexafluoride was determined over the range 2000-26,000 Å (50,000-3900 cm $^{-1}$) and the results are shown in Figure 2. This figure illustrates the variation of ε with wave number over the indicated range. The value for ε , the molar absorbancy index, shown in Figure 2, represents the average of at least two determinations, although in most instances three or more values were used. All peak heights were based on four or more determinations. The position of principal peaks and their molar absorbancy indices are tabulated in Table 1.

Pressures were determined by use of a Booth-Cromer(4) pressure transmitter and self-balancing relay whX h was operated as a null indicator, and was connected to a Heise precision gage.

A Cary, Model 14 double-beam, recording egedrophotometer was used for this work. The wavelength calibration of the instrument was checked against a mercury are and was found to deviate only very slightly from the literature values reported for the mercury are, (5) in order to construct the increasing absorption by the empty cell, particularly in the ultraviolet, an empty cell which had been exposed to pluconium hexalimoride was used in the reference beam of the spectruphotometer when determining the ultraviolet reserved the value of absorbance (log I_c/I) directly.

The concentration of plutonium hexafluoride in the cell in units of moles per liter was calculated from the observed pressure and temperature.

All apectral determinations were carried out at unbient laboratory temperatures. Molar absorbancy indices (molar extinction coefficients) were calculated from the measured absorbance and the calculated concentrations, according to the equation.


log Iol sell

where log last the absorbance (optical density), the the molar absorbanck index in liters mole 'cm', the concentration in moles liter', and it is the thickness of the absorbing medium or the length of the light path to the salest ple. The latter was obtained from a knowledge of the dimensions of the makes cell and the thickness of the compressed gashets scaling the quarts windows to the body of the cell. Values for the absorbance were corrected for the absorbance where corrected for the absorbance of the empty cell as determined before and after each determination of the spectrum.

C. Results and Discussion

I. Results

The absorption apertrum of gaseous platonium bexalluoride was determined over the range 2000-26,000 Å (50,000-1900 cm.") and the results are shown in Figure 2. This figure illustrates the variation of a with wave number over the indicated range. The value for 5, the molar absorbancy index, shown in Figure 2, represents the sverage of at least two determinations, although in most instances three or more values were used. All peak beights were based on tour or more determinations. The position of principal peaks and their molar absorbancy indices are tabulated in Table 1.








Figure 2

ABSORPTION SPECTRUM OF
GASEOUS PLUTONIUM
HEXAFLUORIDE





Pigge S

AUSTORYA MONTHANA

AUSTORYA

Table 1

ABSORPTION SPECTRUM OF GASEOUS PLUTONIUM HEXAFLUORIDE

Principal Peaks

Instrument: Cary, Model 14

Temperature: 22 ± 1°C

Cell Lengths: 1, 5, and 10 cm Pressures: 5-90 mm Hg Window: Quartz

λ (\mathring{A})(a)	$\overline{\nu}$ (cm ⁻¹)	$\epsilon^{(b)}$ (ℓ mole ⁻¹ cm ⁻¹)	f(g)
21150	4728	1.7	11 x 10 ⁻⁷
10435 ± 1	9583	11.8	4.3×10^{-7}
10245 ± 1	9761	8.9	5.7×10^{-7}
10075 ± 1	9926	26.6(e)	19×10^{-7}
9870 ± 1	10132	3.7	2.2×10^{-7}
9734 ± 1	10273	3.2	1.6×10^{-7}
9362 + 1	10681	6.7	1.8×10^{-7}
8374(c)	11940	5.7	12×10^{-7}
8157 ± 5	12260	7.6	17×10^{-7}
7974(c)	12540	6.3	-
7860 ± 2	12720	8.5	14×10^{-7}
7500(c)	13330	2.1	-
5834(c)	17140	4.1	
5614 ± 5	17810	7.0	28×10^{-7}
5418(c)	18460	3.6	-
4371 ± 5	22880	14.5	160×10^{-7}
4259(c)	23480	13.9	-
4139(c)	24160	15.5	_
3157(d)	31680	1055(f)	2.7×10^{-2}
2500(d)	40000	1925	6.0×10^{-2}
2250(d)	44440	2730	9.0×10^{-2}
2090(c)	47850	3685	

- (a) Error in λ obtained as the average deviation of several scans. The wavelength of all sharp peaks have been corrected by use of a standard mercury arc.
- (b) Based on at least four determinations at each peak.
- (c) Broad peak.
- (d) Very broad peak.
- (e) Average deviation ±0.6.
- (f) Average deviation ± 80 .
- $(g)_f = (4.60 \times 10^{-9}) \epsilon_{\max} \Delta \nu_{1/2}$ (Ref. 6).

ABSDRETION SPECTRUM OF GASEOUS PLUTONIUM REXAFLUORIDE

Principal Poaks

Instrument, Cary Model 14
Temperature: 24 1°C
Ceil Lengths: 1, 5, and 10 cm
Pressures: 5-90 mm Hg
Window: Quarts

- (a) Error in A cotained as the average deviation of several scans. The savelength of all sharp peaks have been corrected by use of a stand
 - (b) Based on at least four determinations at each peak
 - (c) Broad peak,
 - d) Very broad peak
 - (c) Average deviation ±0.6.
 - (1) Average deviation ±80.
 - (g) f = (4,60 x 10+9) c max Aviz (Ref. 6)

Included in Table 1 are values of f, the oscillator strength, (6) for those bands believed important. These values may be useful to those wishing to carry out a theoretical analysis of the absorption spectrum.


In order to determine the utility of several of the observed peaks for analysis of plutonium hexafluoride in mixtures, Beer's law plots for the absorption at 10,075 Å and 3157 Å were constructed. These, (see Figures 3 and 4) show no significant deviation from linearity.


Figure 3

BEER'S LAW PLOT FOR GASEOUS PLUTONIUM HEXAFLUORIDE AT 3157 Å

Figure 4

BEER'S LAW PLOT FOR GASEOUS PLUTONIUM HEXAFLUORIDE AT 10075 Å





108-6874

108-6882

The absorption spectrum in the near-infrared region shows two prominent bands which exhibit observable fine structure. The peak separations observed in the spectrum are tabulated in Table 2, together

PEAK SEPARATIONS FOR SEVERAL BANDS IN THE ABSORPTION SPECTRUM OF GASEOUS PLUTONIUM HEXAFLUORIDE

Band Center (cm ⁻¹)a	Peak Separation (cm ⁻¹) b	Pertinent Vibrational Frequency C (cm-1)	Band Center (cm ⁻¹)a	Peak Separation (cm ⁻¹) b	Pertinent Vibrational Frequency (cm ⁻¹)
	175	V ₆ 171	12720	180	v ₆ 171
4728		v6 171		185	V6 171
	178	v5 211		135	
	224	05 211		315	V2-V4 320
	223	V5 211		145	
5975	375				
3113	450	Marie Land	17810	265	
				220	ν ₅ 211
9926	230	V5 211		450	V4 + V5 414
	178	V ₆ 171		640	v ₁ 628
	165	V6 171			
	206	V4 or V5	22880	235	v5 211
	141			360	V2-V6 352
	102			560	v ₂ 523
	75			580	v ₂ 523
	125			350	v2-v6 352
	106			340	V2-V6 352
	106				

a Position of either the center of the band or the principal peak in the band.

b Determined from a plot of wave number versus molar absorbancy,

Correlation made using only fundamental frequencies (v) to vo) or combinations observed in the infrared spectrum of gaseous plutonium hexafluoride.


Included in Table 1 are values of f, the oscillator strength, (6) for those bands believed important. These values may be useful to those wishing to carry out a theoretical analysis of the absorption spectrum.


n order to determine the utility of several of the observed peaks for analysis of plutonium hexafluoride in mixtures. Beer's law plots for the absorption at 10,075 Å and 3157 Å were constructed. These, (see Figures 3 and 4) show no significant deviation from linearity.

Figure 3

Figure 4

BEER'S LAW PLOT FOR CASEOUS
PLUTONIUM HEXAFLUORIDE
AT 19016 Å





sees on

108-6882

The absorption spectrum in the near-infrared region shows two prominent bands which exhibit observable fine structure. The peak separations observed in the spectrum are tabulated in Table 2, together

T SHIPT THE STORMS IN THE RESTORMS OF THE PROPERTY OF THE PROP

threat with me down becoming and to have been been been added and to the de recible of t

STREET ST

with the observed peak separations for those bands which permit such calculations.* Since it is likely that the observed fine structure represents the vibrational energy levels of plutonium hexafluoride, the data in Table 2 are supplemented by a list of the fundamental vibrational frequencies observed in the infrared region. (7)

2. Discussion

The only literature reference to the absorption spectrum of plutonium hexafluoride in which experimental data are presented is that of Goodman, (8) who showed the observed peaks in the spectrum of plutonium hexafluoride. His results, although not extending very far into the ultraviolet and also not containing any data which permit evaluation of the molar absorbancy, agree with the present work in the position of the observed peaks. Goodman developed a discussion of the spectrum of plutonium hexafluoride from the theoretical viewpoint and calculated the energies of peaks expected for plutonium hexafluoride. Jorgensen (9) also has discussed the spectrum of plutonium hexafluoride from the theoretical viewpoint of the electronic configurations of the actinides.

Spectra of species in the isoelectronic series U(IV), Np(V), and Pu(VI) may be compared in order to determine the similarities which exist due to the common electronic structure of the central heavy ion. Although direct comparison is made difficult by absence of data taken from similar compounds, certain similarities can be pointed out. The absorption spectrum of U(IV) in fused CsCl at 825°C shows peaks at 11,000 Å (9091 cm $^{-1}$) and 20,250 Å (4938 cm $^{-1}$) $^{(10)}$ which correlate with the peaks at 10,435 Å and 21,150 Å in plutonium hexafluoride. Several of the peaks observed in the spectrum of U(IV) in aqueous solution $^{(11)}$ can be correlated with those observed in gaseous plutonium hexafluoride. The spectrum of Np(V) in both aqueous solution $^{(12)}$ and in fused nitrate salts $^{(13)}$ shows strong peaks at 9830 Å and at 6170 Å, the former corresponding to the 9870 Å peak observed in gaseous plutonium hexafluoride. The interested reader is referred to the cited literature, particularly the work of Goodman, for discussions of the interpretation of the spectrum of plutonium hexafluoride.

II. ANALYSIS OF MIXTURES OF PLUTONIUM HEXAFLUORIDE AND URANIUM HEXAFLUORIDE BY ABSORPTION SPECTROMETRY

A. Introduction

The Fluid Bed Fluoride Volatility Process involves the fluorination of oxide fuel elements with elemental fluorine which converts uranium and plutonium to the hexafluorides (14) The hexafluorides are separated from most of the fission products by distillation. In this and subsequent operations, gaseous mixtures of the hexafluorides must be handled, and a simple,

^{*}The peak separation data shown in Table 2 have been taken directly from the observed data; only the major peaks are listed in Table 1.

with the observed peak separations for those bands which permit such calculations. Since it is likely that the observed fine attracture copressents the distributional onergy levels of phitomism hexafination, the data in Table 2 are supplemented by a list of the fundamental vibrational frequencies observed in the unrared region. (7)

Discussion

The only literature reference to the absorption appetrum of plus bonium hexallustide in which experimental data are presented a that of Coodman, (8) who showed the objected peaks in the spectrum of plushments bette fluoride. This results, although not extending very farging the of the molar violat and also not containing any data, which permit evaluation of the molar absorbancy, agree with the present work in the position of the conserved peaks. Coodman developed a discussion of the spectrum of plutonium hexallustide from the theoretical viewpoint and calculated the savinges of peaks expectrum of plutonium hexallustide from the theoretical viewpoint of the configurations of the activides.

Exectra of species in the isoelectronic series U(1V), Mp(V), and Du(VI) may be dompared in order to determine the similarities which exist due to the common electronic structure of the central many ion. Although direct comparison is made difficult by absence of data taken from similarities compounds, certain similarities can be pointed out. The absorption space trum of U(IV) in fixed CaCl at 825°C shows peaks at 11,000 Å (9091 cm⁻¹) and 20,250 Å (4938 cm⁻¹) (10) which correlats with the scatte at 10,655 Å such such a plutonium hexalinoride. Several of the scatte at 10,655 Å such served in the spectrum of U(IV) in aqueous solution(11) can be correlated with those one served in gaseous plutonium hexalinoride. The spectrum of tip(V) in both aqueous relution(12) and in fused affiners asitis(13) shows attong peaks at in gaseous plutonium hexalinoride. The interpretated reader here of the spectrum of plutonium bexalinoride. The interpretation of the spectrum of plutonium bexalinoride. The interpretation of the spectrum of plutonium bexalinoride.

II. ANALYSIS OF MIXTURES OF PLUTONIUM HEXAFLUORIDE AND URANIUM HEXAFLUORIDE BY ARSORPTION SPECTROMETRY

noltouboring d

The Fluid Bed Fluoride Volatility Process involves the fluorination of oxide fuel elements with elem intal fluorine which converts undnium and plutonium to the hexalluorides. (*) The hexalluorides are separated from most of the flaston products by distillation.) In this and subsequent opense tions, gascous mixtures of the hexalluorides must be handled, and a simple

The peak apprented data shown in Table 2 have been taken directly from the observed datas unity the major peaks are listed in Table).

nondestructive method of analysis for plutonium hexafluoride in such mixtures is desirable. A method based on the absorption spectra of the hexafluorides was developed for use in the process. Other applications of this method, particularly in laboratory investigations, are believed to be feasible.

B. Experimental

Plutonium hexafluoride was prepared and purified as outlined previously in this report. Uranium hexafluoride, obtained from AEC sources, was purified in a manner similar to that used for plutonium hexafluoride. The vapor pressure of uranium hexafluoride, used as a criterion of purity, was compared with the literature value. (15) Mixtures of plutonium hexafluoride and uranium hexafluoride were made manometrically. In order to obtain a check on the accuracy of the manometric technique, samples of the mixture were hydrolyzed by aqueous nitric acid-aluminum nitrate, and plutonium and uranium were determined in the resulting solution. Plutonium was determined by alpha counting of aliquots of the solution (±2 percent) and uranium was determined by a colorimetric procedure (±2 percent). (16) The agreement between the chemical analysis and the manometric data were, in general, satisfactory except at low plutonium concentrations, for which the manometric data are believed to be more reliable.

The determination of the absorbancy of the mixture was carried out in the same manner as described for pure plutonium hexafluoride in Section I of this report. Spectral analyses were carried out both with a Beckman Model DU and a Cary Model 14 spectrophotometer. Comparison of the two instruments revealed little difference in the measured absorbancies of the mixtures (\pm one percent). One of the peaks used for analysis of the mixtures was the very sharp peak at 10075 Å. The Cary instrument proved more suitable at this wavelength since wavelength adjustments could be made more precisely than in the case of the Beckman.

Two wavelengths were chosen arbitrarily for use in the analysis. The first, at 3157 Å, is applicable for relatively low concentrations of plutonium hexafluoride. Uranium hexafluoride also absorbs at this wavelength,(17) and the molar absorbancy index of uranium hexafluoride was determined as $16 \pm 1 \ \text{$\ell$}$ mole⁻¹cm⁻¹. The corresponding value for plutonium hexafluoride is $1055 \pm 80 \ \text{$\ell$}$ mole⁻¹cm⁻¹. The other wavelength, useful for larger concentrations of plutonium hexafluoride, is the sharp peak at $10075 \ \text{Å}$, where uranium hexafluoride is transparent. Plutonium hexafluoride has a molar absorbancy index of $26.6 \pm 0.6 \ \text{$\ell$}$ mole⁻¹cm⁻¹.

C. Results and Discussion

The results of the analyses of mixtures of plutonium hexafluoride and uranium hexafluoride are shown in Table 3 and in Figures 5 and 6. The molar absorbancy index (molar extinction coefficient) of the mixture, shown in

11

nondestructive method of analysis for plutonium hexafluoride in such mixtures is desirable. A method based on the absorption spectra of the hexafluorides was developed for use in the process. Other applications of this method, particularly in laboratory investigations, ere behaves to be reasible

B. Experiments

Plutonium hexalization ide was prepared and purified as outlined priviously in this report. Uranium hexalization, obtained from AEC sources, was purified in a manner similar to that used for plotonium hexalization of purific, the vapor pressure of transium hexalization, used as a criterion of purify, was compared with the literature, value. Us) Mixingles of plotonium hexalization and uranium hexalization were made mannerically. In order to obtain a check on the accuracy of the mannerically is order to mixture were hydrolyzed by aqueous situation country, and the manner in the solution. Plutonium was determined by a colorimetric processure (12 percent) and arthinum was determined by a colorimetric processure (12 percent) and arthinum was determined by a colorimetric processure (12 percent) and arthinum was determined by a colorimetric processure (12 percent) and arthinum was determined by a colorimetric processure (12 percent) and arthinum satisfactory extept at low plutonium concentrations, for which the manneric data are believed to be more reliable.

The determination of the absorbancy of the mixture was carried out in the same manner as described for pure plutonium hexaliborate in Section of this report. Spectral analyses were carried out both with a Berkmann of this report. Spectrophotometer, Comparison of the two instruments revealed little difference in the measured absorbancies of the mixtures it one percent. One of the poaks mad for analysis of the mastures was the very sharp peak at 100 to A. The Carr instrument proved more sufficiently was this wavelength since wavelength adjustments could be made more uncoisely usen in the case of the Beckmin.

Two wavelengths were chosen arbitrarily for use id the analysis.

The first, at \$157 A, is applicable to: relatively low concentrations of pintonium pexatimentide. Uranium hexatimentide also absorbs at disseaselength (17) and the mular absorbs ney index of uranium hexatimentide was determined as 162 1 A molecular. The corresponding value for phitchium bexatimentide is 1055 180 A molecular. The other wavelength, useful for larger concentrations of plutonium hexatimentide, is the sharp peak at 10075 A, where uranium hexatimentide has a molar absorbatory index of 26.6 ± 0.0 ± molecular.

Results and Discussion

The results of the analyses of mixbures of plutonium bexalluoride and uranium bexalluoride are shown in Table 3 and in Figures 5 and 5. The molar absorbancy index (molar extinction coefficient) of the mixture, shown in

Table 3

DETERMINATION OF THE MOLAR ABSORBANCY INDEX FOR MIXTURES OF PuF6 AND UF6

Instrument: Cary Model 14 or Beckman DU Temperature: Ambient Laboratory (~22°C) Window: Quartz, 3 mm thick

Absorbancy	(log	IO/	I)

	sorbancy nog 10	11/						
Empty Cell before Use	Sample	Empty Cell after Use	Cell Length (cm)	Total P (mm Hg)	λ (Å)	PuF ₆ Cor	ntent (w/o) Chem Anal	ε _m (ℓmole ⁻¹ cm ⁻¹)
Jeiore Ose					-			
0.000	0.070	0.007	1	22.5	3157			54.6
0.007	0.073	0.018	1	20.5	3157			58.2
0.018	0.082	0.027	1	19.5	3157			56.4
						9.5	4.5	
0.001	0.987	0.029	1	47.5	3157			374.5
0.029	0.878	0.041	1	38.5	3157			401.3
0.041	0.451	0.048	1	21.0	3157			355.3
0.042						39.6	36.0	
0.082	0.405	0.088	10	40.5	10075			14.7
0.093	0.396	0.110	10	38.0	10075			14.2
0.110	0.325	0.121	10	27.5	10075			14.0
0.110	0.415	0.138	10	37.0	10075			14.2
0.121	0.415	0.130	10	37.0	10015	49.8	50.1	
0.014	0.367	0.043	10	30.0	10075	47.0	20.1	20.8
0.014	0.392	0.057	10	29.5	10075			21.3
			10	24.5	10075			21.3
0.099	0.390	0.114	10	24.7	10075	74.5	74.7	24.7
				18.5	10075	14.5	14.1	27.3
0.060	0.366	0.125	10					23.8
0.125	0.368	0.159	10	17.5	10075			24.6
0.159	0.389	0.176	10	16.5	10075			26.6
0.216	0.450	0.264	10	14.5	10075			25.3
0.264	0.482	0.300	10	14.5	10075		86.1	25.3
						89.5	86.1	
0.075	0.286	0.087	5 5 5	49.5	10075			15.3
0.087	0.298	0.112	5	49.0	10075			14.9
0.112	0.252	0.117		37.0	10075			13.7
0.123	0.333	0.148	5	47.0	10075			15.4
0.148	0.350	0.174	5	46.0	10075			15.1
0.000	0.594	0.015	1	19.0	3157			569
0.001	0.625	0.040	1	19.5	3157			573
0.000	0.461	0.000	1	17.0	3157			500
0.000	0.647	0.015	1	25.0	3157			471
0.015	0.685	0.018	1	24.0	3157			513
0.017	0.005					50.3	47.2	
0.000	0.474	0.007	1	45.0	3157			193
0.007	0.534	0.027	1	43.5	3157			219
0.007	0.529	0.043	i	43.0	3157			212
0.027	0.490	0.050		36.0	3157			227
0.045	0.490	0.000	COST SECTION	2010		24.4	16.0	
0.110	0.352	0.132	5	48.0	3157			17.7 UF ₆ only
0.110		0.200	5	57.0	3157			16.0 UF6 only
0.132	0.414	0.229	5	39.0	3157			14.3 UF ₆ only
0.200	0.366	0.229		37.0	3131	0		




Figure 5 $\epsilon_{
m m}$ OF PuF₆-UF₆ MIXTURES AT 10075 Å

33

The last fine to sent to a section to be supply to be able to the section of the

un mention or life through the desirable of the section of the sec


Figure 5 m OF Pull - UF MIXTURES AU 10015 A



Figure 6

cm OF PuF6-UF6 MIXTURES

AT 3157 Å



108-6868

Table 3, was calculated by use of the determined absorbancy of the mixture, corrected by the average absorbancy of the empty cell. It is realized that simple averaging of the absorbancy of the empty cell may result in a small error, but no other procedure short of eliminating the absorbancy of the empty cell altogether leads to better results. The two straight lines, shown in Figures 5 and 6 represent the spread of the calculated values for the molar absorbancy index of the mixtures, based on the established uncertainties for the molar absorbancy indices of the pure components, and assuming the validity of Beer's law for the mixture.


It was established that the spectrum of a one-to-one mixture of plutonium hexafluoride and uranium hexafluoride is identical with the spectrum of the two com-

ponents determined separately, showing no shift in the position of the peaks and showing the absence of new peaks. It may therefore be concluded that there is no significant interaction between gaseous plutonium hexafluoride and uranium hexafluoride.

It should be noted that the validity of Beer's law for plutonium hexafluoride was not tested in the presence of an inert gas and hence deviations may be anticipated when plutonium hexafluoride is mixed with uranium hexafluoride. The size of the squares shown in Figures 5 and 6 reflect the limits of the determined molar absorbancy indices and the composition of the mixtures. Deviations of the molar absorbancy indices of the mixtures from Beer's law may be due to a variety of causes, although the positive deviation, observed at 10075 Å, is relatively unusual.

The results indicate that mixtures of plutonium hexafluoride and uranium hexafluoride can be analyzed by spectrometric techniques. In view of the deviations from Beer's law, observed particularly at 10075 Å, calibration curves must be constructed. The most accurate chemical or manometric means available must be used to determine the composition of the standard mixtures. Further, exposure of the quartz cell windows to mixtures of the hexafluorides should be kept to a minimum, and careful pretreatment is required. It is likely that crystalline calcium fluoride windows may be less reactive toward these mixtures, and those wishing to apply this method should consider testing their use. Further, more precise determination of the molar absorbancy indices of the pure components, coupled with an accurate determination of the composition of standard mixtures, are required

Figure 6 cm OF Full-UP, MIXTURES AT 3157 Å



8888-801

Table 3, was calculated by use of the determined absorbancy of the mixture; corrected by the average absorbancy of the empty cell. It is realized that simple aveeraging of the absorbancy of the empty cell may result in a small error, but no other procedure short of eliminating the absorbancy of the empty cell altogether lands to better results. The two straight lines, shown in Figures 5 and 6 represent the spread of the calculated values for the molar absorbancy index of the mixtures, the molar absorbancy index of the mixtures, the molar absorbancy index of the page components, and assuming the validity of Seer's law for the mixture.

It was established that the spectrum of a one-to-one mixture of plufonium hexafluoride and uranium hexafluoride is whenly all the spectrum of the two corons

ponents determined separately, showing no shift in the position of the pester and showing the absence of new peaks. It may therefore be concluded that there is no significant interaction between gaseous plufonium hexalluoride and uranium hexalluoride.

It should be noted that the validity of Beer's law for plulontum home. Should was not tested in the presence of an inert gas, and hence deviations may be anticipated when plutonium hexafluoride is mixed with uranium hexafluoride. The size of the squares shown in Figures 5 and 6 reflect the limits of the determined molar absorbancy indices and the composition of the mixtures. Deviations of the molar absorbancy indices of the mixtures from Beer's law may be due to a variety of causes, although the positive deviation observed at 10075 Å, is relatively unusual.

The results indicate that mixtures of plutonium hexafluoride and uranium hexafluoride can be analyzed by spectrometric rechaiques. In view of the deviations from Beer's law, observed particularly at 10075 Å. calibration curves must be constructed. The most accurate chemical or manometric means available must be geed to determine the composition of the standard mixtures. Further, exposure of the quartz cell windows to mixtures of the hexafluorides should be kept to a minimum, and careful protreatment is required. It is likely that crystalline calcum fluoride windows may be less reactive toward these mixtures, and those wishing to apply this method should consider testing their use. Further, more precise determination of the molar absorbancy indices of the pure components, coupled with an accurate determination of the composition of standard mixtures, are required curate determination of the composition of standard mixtures, are required

to improve the precision of the method of analysis. Finally, it is likely that suitable calibration curves could be developed for mixtures which also contain elemental fluorine.

ACKNOW LEDGMENT

The authors wish to acknowledge the support of Dr. J. Fischer, the aid of D. V. Steidl and C. Trindle with some of the experimental work, and C. A. Seils for the analyses of the mixtures.

to improve the precision of the method of analysis. Finally, it is likely that suitable fallbration curves could to developed for mixtures which also constain elemental fluoring.

CHOYOUT ENGLISHED

The authors wish to acknowledge the support of Dr. J. Nacher, the sid of Dr. V. Sieidl and C. Trindle with some of the experimental work, and C. A. Seils for the analyses of the mixtures

BIBLIOGRAPHY

- 1. Steindler, M. J., Steidl, D. V., and Steunenberg, R. K., Nucl. Sci. and Eng., 6, 333 (1959).
- Weinstock, B., Weaver, E. E., and Malm, J. G., J. Inorg. Nucl. Chem., 11, 104 (1959).
- Steindler, M. J., Steidl, D. V., and Steunenberg, R. K., ANL-5875 (1958).
- 4. Cromer, S., MDDC-803 (1944).
- 5. Gibson, K. S., NBS Circular 484 (1949), p. 12.
- 6. Beaven, G. H., et al., Molecular Spectroscopy, Maywood and Company Limited (1961), p. 14.
- Malm, J. G., Weinstock, B., and Claasen, H. H., J. Chem. Phys., <u>23</u>, 2192 (1955).
- 8. Goodman, G. L., Thesis, Harvard University (1959).
- 9. Jorgensen, C. K., Mol. Phys., 2, 96 (1959).
- 10. Morrey, J. R., unpublished data.
- 11. Howland, J. J., TID-5290, paper 66.
- 12. Sjoblom, R., and Hindman, J. C., J. Am. Chem. Soc., 73, 1744 (1951).
- 13. Gruen, D. M., Graf, P., and Fried, S., XVIth Int. Congr. Pure and Appl. Chem., 1957, p. 319.
- 14. See Part I of this series, ANL-6742 (1963).
- Oliver, G. D., Milton, H. T., and Grisard, J. W., J. Am. Chem. Soc., 75, 2827 (1953).
- 16a. Francois, C. A., Anal. Chem., 30, 50 (1958).
- 16b. Maeck, W. J., et al., Anal. Chem., 31, 1130 (1959).
- 17. Steunenberg, R. K., ANL-5254 (1954), p. 49.

SIBLIOGRAPHY

- Steindler, M. J., Steidl, D. V., and Steinenberg, R. K., ANL-5875 (1958).
 - Cromer, S., MDDC-803 (1944)
 - 5. Gibson, K. S. NBS Circular 484 (1949), p. 12.
 - b. Beaven, G. H., et al., Molecular Spectroscopy, Maywood and Company Limited (1961), p. 14.
- Malm. J. G., Weinstock, B., and Classen, H. H., J. Chem. Phys., 23, 2192 (1955).
 - 8 Goodman, G. L., Thesis, Harvard University (1959)
 - 9. 1 Jorgensen, C. K. Mol. Phys. 2, 96 (1959).
 - 10. Morrey, J. R. unpublished date
 - 11. Howland J. J., TID-5290 paper 50
- 12. Steblom, R., and Hindman, J. C., J. Am. Chem. Soc., 73, 1744 (1951).
 - Cruen, D. M., Orel, P., and Tried, S., XVIth Int. Congr. Pure and Appl. Chem., 1957, p. 319.
 - 14. See Part 1 of this series ANL-5742 (1963)
 - Oliver, G. D., Milton, H. T., and Greatd, J. W., J. Am. Chem. Sect. 75, 2827 (1953).
 - 16a. Francois, C. A. Anal. Chom., 30, 50 (1958)
 - 16b. Maeck, W. J., et al. Anal. Chem. 31, 3130 (1959
 - Steunenburg, R. K., ANL-5254 (1954), p. 49

